

# Professional Testing Laboratory, LLC. Test Request/Chain of Custody Form

714 Glenwood Place • Dalton, GA 30721 • Phone: 706-226-3283 • Fax: 706-226-6787 • testing@professionaltesting.us

<b>Company</b>		<b>Date</b>	/ /
<b>Name</b>		<b>Submitted</b>	
<b>Address</b>		<b>PO#</b>	
<b>City/State/Zip</b>		<b>Authorized By:</b>	
<b>E-Mail</b>		<b>Need by Date:</b>	/ /
<b>Phone</b>		<b>SIGNATURE</b>	

## Sample Information

<b>Identification</b>	<b>Construction</b>
<b>Color</b>	<b>Type</b>
<b>Roll</b>	<b>Backing</b>
<b>Claim #:</b>	<b>Reference</b>

## Test(s) Required (Please check appropriate boxes)

<p><b>SLIP RESISTANCE TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM D2047 James Machine Specify (Neolite/Leather-- Wet/Dry)</li> <li><input type="checkbox"/> ASTM E303 Pendulum Slip</li> <li><input type="checkbox"/> ASTM C1028 Coefficient of Friction</li> <li><input type="checkbox"/> ANSI A137 Coefficient of Friction</li> <li><input type="checkbox"/> ANSI B101.3 Coefficient of Friction</li> <li><input type="checkbox"/> ASTM D2394 Coefficient of Friction</li> <li><input type="checkbox"/> ASTM F2913 Slip Performance</li> <li><input type="checkbox"/> BMS-286C Coefficient of Friction</li> <li><input type="checkbox"/> BSS 7392 Coefficient of Friction</li> <li><input type="checkbox"/> FAA(FAR 25.793) Sliding Friction</li> <li><input type="checkbox"/> MIL-W-5044 Sliding Friction</li> <li><input type="checkbox"/> ASTM D1894 Coefficient of Friction</li> <li><input type="checkbox"/> EN 13893 Slip Resistance</li> <li><input type="checkbox"/> UL 410 Slip Resistance</li> <li><input type="checkbox"/> BS EN 16165</li> </ul> <p><b>ABRASION/SCRATCH TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM D4060 Abrasion ( # cycles)***</li> <li><input type="checkbox"/> ASTM D7027 Hoffman Scratch</li> <li><input type="checkbox"/> EN 16094 Micro Scratch</li> <li><input type="checkbox"/> ASTM F510 Grit Feeder Abrasion</li> <li><input type="checkbox"/> BS EN 660 Abrasion (Frick Test)</li> <li><input type="checkbox"/> EN 13329 Abrasion Classification</li> <li><input type="checkbox"/> ISO 24338 Abrasion Resistance of Laminate Flooring</li> <li><input type="checkbox"/> EN 14565 Appendix A Microscratch</li> <li><input type="checkbox"/> ISO 1518-1 Determination of Scratch Resistance</li> <li><input type="checkbox"/> Sim Floor Straight Line Scratch</li> <li><input type="checkbox"/> ASTM D3363 Film Hardness</li> <li><input type="checkbox"/> ASTM D2197 Adhesion by Scrape (Belmar Loop)</li> </ul> <p><b>OTHER TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> AATCC 134 Static</li> <li><input type="checkbox"/> ASTM G21 Anti-Fungal</li> <li><input type="checkbox"/> ASTM D6007 Small Chamber Formaldehyde</li> <li><input type="checkbox"/> CPSC-CH-C001-09.4 Ortho Phthalates</li> <li><input type="checkbox"/> EPA Method 3052 Heavy Metals</li> <li><input type="checkbox"/> CPSC-CH-E1002-08.3 Heavy Metals Content</li> <li><input type="checkbox"/></li> <li><input type="checkbox"/></li> </ul>	<p><b>RESILIENT PERFORMANCE</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ISO 4918 Chair Caster ( # of cycles)</li> <li><input type="checkbox"/> ISO 23999 Dimensional/Planar Stability</li> <li><input type="checkbox"/> ISO 24337 Flatness, Openings, Ledgings</li> <li><input type="checkbox"/> ASTM F2055 Size &amp; Squareness</li> <li><input type="checkbox"/> ASTM F2199 Dimensional/Planar Stability</li> <li><input type="checkbox"/> ASTM F2421 Size &amp; Squareness</li> <li><input type="checkbox"/> ASTM F3414 CPSC Phthalates</li> <li><input type="checkbox"/> ASTM F137 Flexibility</li> <li><input type="checkbox"/> ASTM F386 Thickness</li> <li><input type="checkbox"/> ASTM F387 Thickness with pad</li> <li><input type="checkbox"/> ASTM F410 Thickness</li> <li><input type="checkbox"/> ASTM F970 Static Load (List PSI ____ or Max)</li> <li><input type="checkbox"/> ASTM F1265 Impact</li> <li><input type="checkbox"/> ASTM F1304 Deflection</li> <li><input type="checkbox"/> ASTM F1514 Resistance To Heat</li> <li><input type="checkbox"/> ASTM F1515 Resistance To Light</li> <li><input type="checkbox"/> ASTM F1914 Indentation</li> <li><input type="checkbox"/> ASTM F1914 Indentation + Surface integrity</li> <li><input type="checkbox"/> ISO 16581 Chair Leg</li> <li><input type="checkbox"/> ISO 24334 Locking Strength</li> <li><input type="checkbox"/> ASTM D412 Modulus</li> <li><input type="checkbox"/> ASTM F925 Chemical Resistance</li> <li><input type="checkbox"/> ASTM F925 Chemical Resistance <b>with L,a,b, indentation and thickness optional values</b></li> <li><input type="checkbox"/> ASTM D2240 Hardness</li> <li><input type="checkbox"/> ASTM F2772 Sports Floor Classification</li> <li><input type="checkbox"/> ASTM F2117 Ball Bounce</li> <li><input type="checkbox"/> BS EN 12235 Vertical Rebound</li> <li><input type="checkbox"/> DIN 18032 Force Reduction and Vertical Deformation</li> <li><input type="checkbox"/> ASTM F3261 Thickness Swell</li> </ul> <p><b>WOOD PERFORMANCE</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM D3359 Finish Adhesion</li> <li><input type="checkbox"/> ASTM D1037 Janka Hardness</li> <li><input type="checkbox"/> ASTM D2394 Ball Drop Indentation</li> <li><input type="checkbox"/> ANSI HPVA Bond Line Delamination</li> <li><input type="checkbox"/> ASTM D1037 Dimensional Change</li> <li><input type="checkbox"/> ASTM D1308 Staining of Finishes</li> <li><input type="checkbox"/> ASTM D2094 Moisture Content</li> <li><input type="checkbox"/> ASTM D3459 Cycled Environment Exposure</li> </ul> <p><b>ADHESIVE TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM D3167 Floating Roller Peel</li> <li><input type="checkbox"/> ASTM D6004 Shear Strength</li> <li><input type="checkbox"/></li> </ul>	<p><b>FIRE TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM E648 Radiant Panel</li> <li><input type="checkbox"/> ASTM E662 Smoke Density</li> <li><input type="checkbox"/> ASTM E84 Tunnel Test</li> <li><input type="checkbox"/> CAN ULC S102 Tunnel Test</li> <li><input type="checkbox"/> ASTM D635 Rate of Burning</li> <li><input type="checkbox"/> UL 94 Flammability Classification</li> </ul> <p><b>NALFA TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> NALFA 3.1 Static Load</li> <li><input type="checkbox"/> NALFA 3.2 Thickness swell</li> <li><input type="checkbox"/> NALFA 3.3 Compression Resistance</li> <li><input type="checkbox"/> NALFA 3.3 Light resistance</li> <li><input type="checkbox"/> NALFA 3.4 Cleanability</li> <li><input type="checkbox"/> NALFA 3.5 Large Ball Impact</li> <li><input type="checkbox"/> NALFA 3.6 Small Ball Impact</li> <li><input type="checkbox"/> NALFA 3.7 Wear Resistance Taber</li> <li><input type="checkbox"/> NALFA 3.8 Dimensional Tolerances</li> <li><input type="checkbox"/> NALFA 3.9 Castor Chair</li> <li><input type="checkbox"/> NALFA 3.10 Surface Bonding</li> <li><input type="checkbox"/> NALFA 3.12, 3.13, 3.14 Determination of Flatness, Openings and Ledging</li> <li><input type="checkbox"/> NALFA Assembled Joint Surface Swell Test</li> <li><input type="checkbox"/> NALFA Macro-scratch</li> <li><input type="checkbox"/> NALFA Stylus Scratch</li> </ul> <p><b>CERAMIC TESTS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> ASTM C1026 Freeze Thaw</li> <li><input type="checkbox"/> ASTM C1027 Visible Abrasion</li> <li><input type="checkbox"/> ASTM C1243 Deep Abrasion</li> <li><input type="checkbox"/> ASTM C648 Breaking Strength</li> <li><input type="checkbox"/> ASTM C1870 Impact Diameter from Falling Ball</li> <li><input type="checkbox"/> ASTM C1895 Mohs Scratch Hardness</li> <li><input type="checkbox"/> ASTM C373 Water Absorption</li> <li><input type="checkbox"/> ASTM C424 Test Method for Craze Resistance</li> <li><input type="checkbox"/> ASTM C482 Bond Strength of Ceramic Tile</li> <li><input type="checkbox"/> ASTM C484 Thermal Shock Resistance</li> <li><input type="checkbox"/> ASTM C485 Warpage Edge/Warpage Diagonal</li> <li><input type="checkbox"/> ASTM C499 Facial Dimensions and Thickness of Flat, Rectangular Ceramic Wall and Floor Tile....</li> <li><input type="checkbox"/> ASTM C502 Wedging of Flat, Rectangular</li> <li><input type="checkbox"/> ASTM C501 Resistance to Wear</li> <li><input type="checkbox"/> ASTM C502 Wedging</li> <li><input type="checkbox"/> ASTM C609 Light Reflectance Value and Color Differences</li> <li><input type="checkbox"/> ASTM C650 Resistance to Chemical Substances</li> <li><input type="checkbox"/> ASTM C880 Flexural Strength of Dimension Stone</li> <li><input type="checkbox"/> ASTM C895 Lead and Cadmium Extracted</li> <li><input type="checkbox"/> ASTM C97 Absorption and Bulk Specific Gravity</li> </ul>
---	--	--

\*TEST RETAINS ARE KEPT FOR A MAXIMUM OF 1 WEEK

<b>RETURN TESTED SAMPLES</b>	YES NO	<b>PRIORITY/RUSH (expedited fee 100% premium)</b>	YES NO
<b>RETURN REMAINING SAMPLES</b>	YES NO	<b>TEST PHOTOS (\$10 each photo)</b>	YES NO
<b>PROVIDE SHIPPING METHOD</b>	ACCT # or add to invoice	<b>SPECIAL INSTRUCTIONS</b>	